

ACCEPTED THERMOPLASTIC MEMBRANE SYSTEMS

Minimum thickness of TPO membranes is 45 mil (1.1 mm). Thicker sheets are also available and accepted by ARCA Warranty Ltd. Membrane seams are sealed by hot-air welding with specialized equipment.

Thermoplastic Polyolefin (T.P.O.) Membrane

Meeting ASTM D-6878 standards

<u>Carlisle TPO Membranes</u>	<u>Attachment Method</u>			<u>ARCA Warranty Certificate</u>		
	Fully Adhered	Mech. Fast.	RhinoBond (Induction Welded)	5 Year	10 Year	15 Year
Sure-Weld 45 mil	●	●		●	●	
Sure-Weld 60 mil	●	●	●	●	●	
Sure-Weld 80 mil	●	●	●	●	●	●
Fleeceback 100 mil	●	●		●	●	
Fleeceback 115 mil	●	●		●	●	
Fleeceback 135 mil	●	●		●	●	●
Approved Adhesives:	Sure-Weld Bonding Adhesive Low VOC Bonding Adhesive for TPO Low VOC Bonding Adhesive 1168 Aqua Base 120 Bonding Adhesive Cav-Grip III Low-VOC Aerosol Contact Adhesive					

<u>Firestone TPO Membranes</u>	<u>Attachment Method</u>			<u>ARCA Warranty Certificate</u>		
	Fully Adhered	Mech. Fast.	Insiweld (Induction Welded)	5 Year	10 Year	15 Year
Ultraply 45 mil	●	●		●	●	
Ultraply 60 mil	●	●	●	●	●	
Ultraply 80 mil	●	●	●	●	●	●
Approved Adhesives:	Water Based Bonding Adhesive Single Ply LVOC Bonding Adhesive Ultraply Bonding Adhesive Jet Bond Spray Adhesive					

<u>IKO TPO Membranes</u>	<u>Attachment Method</u>			<u>ARCA Warranty Certificate</u>		
	Fully Adhered	Mech. Fast.	RhinoBond (Induction Welded)	5 Year	10 Year	15 Year
InnoviTPO 45 mil	●	●		●	●	
InnoviTPO 60 mil	●	●	●	●	●	
InnoviTPO 80 mil	●	●	●	●	●	●
Approved Adhesives:	InnoviBond Membrane Adhesive					